

C-WE-R-KEG

Male Stud Elbow

Male BPP Stud/Connector - Tapered (DN 40x2 Type C) /
2" Tubo-Connector (DN DN ISO 6434-1)



C-WE-R-KEG



Series	DN (inch)	DN (mm)	F	DN (inch)	DN (mm)	A ₁ (mm)	L ₁ (mm)	L ₂ (mm)	A ₂ (mm)	E ₁ (mm)	E ₂ (mm)	Working Load ¹⁾	DN (inch)
IA	100/100	4	40/140.0	5.0	40.0	15	112.0	17	21	8	10	2,000 kg (4,400 lb)	1.2
		6	40/140.0	6.0	40.0	15	84.0	17	21	8	10	2,000 kg (4,400 lb)	1.2
		8	40/140.0	8.0	80.0	17	74.0	20	23	10	10	2,000 kg (4,400 lb)	1.4
		10	40/140.0	10.0	70.0	18	76.0	20	27	12	10	2,000 kg (4,400 lb)	1.6
		12	40/140.0	12.0	70.0	18	76.0	27	27	14	10	2,000 kg (4,400 lb)	1.8
L	275/275	4	40/140.0	4.0	40.0	19	122.0	20	27	12	14	2,000 kg (4,400 lb)	1.2
		6	40/140.0	6.0	60.0	20	100.0	20	26	12	14	2,000 kg (4,400 lb)	1.4
		8	40/140.0	8.0	80.0	21	142.0	20	26	12	14	2,000 kg (4,400 lb)	1.6
		10	40/140.0	10.0	80.0	21	142.0	20	26	12	14	2,000 kg (4,400 lb)	1.8
		12	40/140.0	12.0	80.0	21	142.0	20	26	12	14	2,000 kg (4,400 lb)	2.0
		14	40/140.0	14.0	70.0	22	150.0	27	30	14	14	2,000 kg (4,400 lb)	2.2
		16	40/140.0	16.0	80.0	24	172.0	26	32	17	14	2,000 kg (4,400 lb)	2.4
		18	40/140.0	18.0	80.0	24	172.0	26	32	17	14	2,000 kg (4,400 lb)	2.6
		20	40/140.0	20.0	70.0	25	174.0	27	34	17	14	2,000 kg (4,400 lb)	2.8
		22	40/140.0	22.0	70.0	25	174.0	27	34	17	14	2,000 kg (4,400 lb)	3.0
		24	40/140.0	24.0	70.0	26	172.0	27	36	17	14	2,000 kg (4,400 lb)	3.2
		S	400/400	4	40/140.0	4.0	40.0	23	162.0	20	31	12	14
6	40/140.0			6.0	60.0	24	160.0	20	31	12	14	2,000 kg (4,400 lb)	1.6
8	40/140.0			8.0	70.0	25	160.0	20	31	12	14	2,000 kg (4,400 lb)	1.8
10	40/140.0			10.0	70.0	24	172.0	27	32	14	14	2,000 kg (4,400 lb)	2.0
12	40/140.0			12.0	70.0	25	160.0	20	31	12	14	2,000 kg (4,400 lb)	2.2
14	40/140.0			14.0	70.0	26	172.0	26	34	17	14	2,000 kg (4,400 lb)	2.4
16	40/140.0			16.0	80.0	26	172.0	26	34	17	14	2,000 kg (4,400 lb)	2.6
18	40/140.0			18.0	80.0	26	172.0	26	34	17	14	2,000 kg (4,400 lb)	2.8
20	40/140.0			20.0	70.0	27	172.0	27	36	17	14	2,000 kg (4,400 lb)	3.0
22	40/140.0			22.0	80.0	28	172.0	27	36	17	14	2,000 kg (4,400 lb)	3.2
24	40/140.0			24.0	80.0	28	172.0	27	36	17	14	2,000 kg (4,400 lb)	3.4
26	40/140.0			26.0	80.0	28	172.0	27	36	17	14	2,000 kg (4,400 lb)	3.6

¹⁾ Replace the Parameter "F" with "E" when you require short.
C = Standard, D = 1.500, E = 1.500 Standard, F = 1.500